X8 SuperSnake - subfeeder

BENEFITS

- Suitable for Fe/Ss/Al/FCW/MCW filler wires
- 10/15/20/25-meter water-cooled models
- Parameter adjustment with the Control Pad or X8 Gun Remote Control
- Supports all Kemppi Wise special processes
- Strong protective frame included as standard
- A perfect choice for heavy and medium-heavy metal fabrication and installation work

TECHNICAL SPECIFICATIONS

X8 SuperSnake - subfeeder

Product code	See technical specifications
Description	subfeeder
Output 60% ED	310 A
Wire feed mechanism	GT02X, 2-roll
Wire feed speed	0-25 m/min
Feeder body dimensions, L x W x H	777 x 142 x142 mm
Wire recommendations, 15 m	Fe/Ss 1.0-1.6 mm Al 1.2-1.6 mm FeMc/FeFc 1.2-1.6 mm
Cable diameter	50 mm²
Supply voltage	50 V DC
Protection class	IP 23S
Ordering code 10m	X8900501000 - Fe X8900501001 - Ss/Al
Ordering code 15m	X8900501500 - Fe X8900501501 - Ss/Al
Ordering code 20m	X8900502000 - Fe X8900502001 - Ss/Al
Ordering code 25m	X8900502500 - Fe X8900502501 - Ss/Al
Consumables	The wire feed mechanism consumable kit must be ordered separately according to the filler wire material.

X8 SuperSnake - subfeeder /
Technical specifications