

X8 Power Source 400



概览

Provides 400 A with a 60% duty cycle. Can be ordered with or without X8 Cooler. Control Pad always included with the power source.

技术规格

X8 Power Source 400	
产品代码	X8100400001 - X8 Power Source 400, CUSTOM (Work Pack + WiseFusion) X8100401000 - X8 Power Source 400, cooler X8100401001 - X8 Power Source 400, cooler, CUSTOM (Work Pack + WiseFusion)
电源连接电压 3~ 50/60 Hz	380 - 460 V ± 10 %
保险丝	32 A
空载功率 (MMA) (不带冷却器和送丝机, 风扇关闭)	44 - 53 W
空载功率 (MMA) (不带冷却器和送丝机, 风扇打开)	107 - 111 W
空载功率 (MMA) (带冷却器, 不带送丝机, 风扇打开)	132 - 137 W
输出 60% ED	400 A
输出 100% 暂载率	320 A
焊接电流和电压范围, MIG @ 380 V	20A/14V - 400A/50V
焊接电流和电压范围, MMA @ 380 V	15A/20V - 400A/58V
建议的发电机功率 (最小)	25 kVA
空载电压 (MMA)	50 V
工作温度范围	-20...+40 °C
外部尺寸 (长 x 宽 x 高)	921 x 348 x 795 mm
重量 (无配件)	95 kg