

MinarcTig 250



TEKNISKE SPECIFIKATIONER

MinarcTig 250

Produktkode	MinarcTig 250, TX 165GF 4M –P0607TX MinarcTig 250, TX 165GF 8M – P0608TX MinarcTig 250, TX 225G 4M – P0609TX MinarcTig 250, TX 225G 8M – P0610TX MinarcTig 250, TX 165GS 4M – P0625TX MinarcTig 250, TX 165GS 8M – P0626TX MinarcTig 250, TX 225GS 4M – P0632TX MinarcTig 250, TX 225GS 8M – P0633TX MinarcTig 250, TX 135GF 4M – P0636TX MinarcTig 250, TX 135GF 8M – P0637TX MinarcTig 250, TX 165GS 16M – P0668TX
Netspænding 3~ 50/60 Hz	400 V -20...+15 %
Sikring (træg)	10 A
Output (TIG) 30% ED	250 A/20,1 V (30 %)
Output (TIG) 100% ED	160 A/16,4 V (100 %)
Output (MMA) 35% ED	220 A /28,8 V (35 %)
Output (MMA) 100% ED	150 A/26,0 V (100 %)
Tomgangsspænding	95 V (VRD 30 V)
Stavelektrodestørrelser	1,5...5,0 mm
Svejseområde (MMA)	10 A/20,4 V-220 A/28,8 V
Svejseområde (TIG)	5 A/10,2 V-250 A/20,1 V
Driftstemperaturområde	-20 ... +40 °C
Udvendige mål L x B x H	400 × 180 × 340 mm
Vægt (uden tilbehør)	11 kg (uden kabler)
Kapslingsklasse	IP23S