

MinarcTig Evo

SMOOTH, REFINED AND POWERFUL

28.11.2021



And you know.



TECHNICAL SPECIFICATIONS

MinarcTig Evo 200

Product code	MinarcTig Evo 200, TX 225G 4M – P0640TX MinarcTig Evo 200, TX 225G 8M – P0641TX MinarcTig Evo 200, TX 225GS 8M – P0645TX MinarcTig Evo 200, TX 165GS 4M – P0648TX MinarcTig Evo 200, TX 165GS 8M – P0649TX MinarcTig Evo 200, TX 135GF 4M – P0652TX MinarcTig Evo 200, TX 135GF 8M – P0653TX MinarcTig Evo 200, TX 165GF 4M – P0656TX MinarcTig Evo 200, TX 165GF 8M – P0657TX MinarcTig Evo 200, TX 225GS 4M – P0644TX MinarcTig Evo 200, TX 165GS 16M – P0670TX MinarcTig Evo 200, TX 305WF 4M, COOLER – P0676TX MinarcTig Evo 200, TX 305WF 8M, COOLER – P0677TX MinarcTig Evo 200, TX 255WS 4M, COOLER – P0687TX MinarcTig Evo 200, TX 255WS 8M, COOLER – P0688TX MinarcTig Evo 200, TX 355W 4M, COOLER – P0691TX MinarcTig Evo 200, TX 355W 8M, COOLER – P0692TX
Connection voltage 1~ 50/60 Hz	230 V ±15 %
Fuse (delayed)	16 A
Minimum generator power	5.6kVA
Output (TIG) 35% ED	200 A/18.0 V
Output (TIG) 60% ED	160 A/16.4 V
Output (TIG) 100% ED	140 A/15.6 V
Output (MMA) 35% ED	170 A/26.8 V
Output (MMA) 60% ED	130 A/25.2 V
Output (MMA) 100% ED	110 A/24.4 V
Open circuit voltage	95 V
Stick electrode sizes	1.5...4.0 mm
Welding range (MMA)	10 A /20.4 V...170 A/26.8 V
Welding range (TIG)	5 A/10.2 V...200 A/18.0 V
Operating temperature range	-20...+40 °C
External dimensions LxWxH	449 × 210 × 358 mm
Weight (no accessories)	11 kg
Degree of protection	IP23S
Standards	IEC 60974-1, IEC 60974-3, IEC 60974-10, IEC 61000-3-12



MinarcTig Evo 200MLP

Product code	MinarcTig Evo 200MLP, TX 225G 4M – P0642TX MinarcTig Evo 200MLP, TX 225G 8M – P0643TX MinarcTig Evo 200MLP, TX 225GS 8M – P0647TX MinarcTig Evo 200MLP, TX 165GS 4M – P0650TX MinarcTig Evo 200MLP, TX 165GS 8M – P0651TX MinarcTig Evo 200MLP, TX 135GF 4M – P0654TX MinarcTig Evo 200MLP, TX 135GF 8M – P0655TX MinarcTig Evo 200MLP, TX 165GF 4M – P0658TX MinarcTig Evo 200MLP, TX 165GF 8M – P0659TX MinarcTig Evo 200MLP, TX 165GS 16M – P0671TX MinarcTig Evo 200MLP, TX 225GS 4M – P0646TX MinarcTig Evo 200MLP, TX 305WF 4M, COOLER – P0678TX MinarcTig Evo 200MLP, TX 305WF 8M, COOLER – P0679TX MinarcTig Evo 200MLP, TX 255WS 4M, COOLER – P0689TX MinarcTig Evo 200MLP, TX 255WS 8M, COOLER – P0690TX MinarcTig Evo 200MLP, TX 355W 4M, COOLER – P0693TX MinarcTig Evo 200MLP, TX 355W 8M, COOLER – P0694TX
Connection voltage 1~ 50/60 Hz	230 V ±15 %
Fuse (delayed)	16 A
Minimum generator power	5.6kVA
Output (TIG) 35% ED	200 A/18.0 V
Output (TIG) 60% ED	160 A/16.4 V
Output (TIG) 100% ED	140 A/15.6 V
Output (MMA) 35% ED	170 A/26.8 V
Output (MMA) 60% ED	130 A/25.2 V
Output (MMA) 100% ED	110 A/24.4 V
Open circuit voltage	95 V
Stick electrode sizes	1.5...4.0 mm
Welding range (MMA)	10 A /20.4 V...170 A/26.8 V
Welding range (TIG)	5 A/10.2 V...200 A/18.0 V
Operating temperature range	-20...+40 °C
External dimensions LxWxH	449 × 210 × 358 mm
Weight (no accessories)	11 kg
Degree of protection	IP23S
Standards	IEC 60974-1, IEC 60974-3, IEC 60974-10, IEC 61000-3-12



MinarcTig Evo 200 AU

Product code	MinarcTig Evo 200 AU, TX 225G 4M – P0672TX MinarcTig Evo 200 AU, TX 225G 8M – P0673TX
Connection voltage 1~ 50/60 Hz	240 V ±15 %
Fuse (delayed)	16 A
Minimum generator power	5.6kVA
Output (TIG) 35% ED	200 A/18.0 V
Output (TIG) 60% ED	160 A/16.4 V
Output (TIG) 100% ED	140 A/15.6 V
Output (MMA) 35% ED	170 A /26.8 V (35 %)
Output (MMA) 60% ED	130 A/25.2 V
Output (MMA) 100% ED	110 A/24.4 V
Open circuit voltage	95 V
Stick electrode sizes	1.5...4.0 mm
Welding range (MMA)	10 A /20.4 V...170 A/26.8 V
Welding range (TIG)	5 A/10.2 V...200 A/18.0 V
Operating temperature range	-20...+40 °C
External dimensions LxWxH	449 × 210 × 358 mm
Weight (no accessories)	11 kg
Degree of protection	IP23S
Standards	IEC 60974-1, IEC 60974-3, IEC 60974-10, IEC 61000-3-12

MinarcTig Evo 200MLP AU

Product code	MinarcTig Evo 200MLP AU, TX 225G 4M – P0674TX MinarcTig Evo 200MLP AU, TX 225G 8M – P0675TX
Connection voltage 1~ 50/60 Hz	240 V ±15 %
Fuse (delayed)	16 A
Minimum generator power	5.6kVA
Output (TIG) 35% ED	200 A/18.0 V
Output (TIG) 60% ED	160 A/16.4 V
Output (TIG) 100% ED	140 A/15.6 V
Output (MMA) 35% ED	170 A /26.8 V
Output (MMA) 60% ED	130 A/25.2 V
Output (MMA) 100% ED	110 A/24.4 V
Open circuit voltage	95 V
Stick electrode sizes	1.5...4.0 mm
Welding range (MMA)	10 A/20.4 V...170 A/26.8 V
Welding range (TIG)	5 A/10.2 V...200 A/18.0 V
Operating temperature range	-20...+40 °C
External dimensions LxWxH	449 × 210 × 358 mm
Weight (no accessories)	11 kg
Degree of protection	IP23S
Standards	IEC 60974-1, IEC 60974-3, IEC 60974-10, IEC 61000-3-12



ACCESSORIES

Mastercool 20

Product code	6162900 - Mastercool 20 6162901 - Mastercool 20 for MinarcTig Evo
Connection voltage 1~ 50/60 Hz	230 V ±15 %
Rated power	50 W (100 %)
Operating temperature range	-20...+40 °C
External dimensions LxWxH	500 × 180 × 260 mm
Weight (no accessories)	8 kg
Degree of protection	IP23C
Cooler tank volume	approx. 3 l
Cooling power	1.0 kW

Welding cable 5 m 25 mm²

Product code	6184201
--------------	---------

Welding cable 10 m 25 mm²

Product code	6184202
--------------	---------

Earth return cable 10 m, 25 mm²

Product code	6184212
--------------	---------

Earth return cable 5 m, 25 mm²

Product code	6184211
--------------	---------

MST 400

Product code	6185294
--------------	---------

Shoulder strap

Product code	9592163
--------------	---------

Remote control R10

Product code	R10, 5 m - 6185409 R10, 10 m - 618540901
--------------	---

Remote control R11F

Product code	6185407
--------------	---------



TXR10

Description	remote control
Product code	TXR10W / TXR10G

TXR20

Description	remote control
Product code	TXR20W / TXR20G

WWW.KEMPPI.COM

Kemppi is the pioneering company within the welding industry. It is our role to develop solutions that make you win business. Headquartered in Lahti, Finland, Kemppi employs over 800 welding experts in 17 countries and has a revenue of more than 150 MEUR. Our offering includes welding solutions - intelligent equipment, welding management software and expert services - for both demanding industrial applications and ready-to-weld needs. Local expertise is available via our global partner network covering over 60 countries.

