

A7 Wire Feeder 25



OVERVIEW

The A7 Wire Feeder 25 is a durable and powerful two motor for 4-wheel feeding system designed to work seamlessly with A7 MIG Welder power sources. A separate attachment bracket is required for mounting the wire feeder on robot.

Integrated functionalities:

- Gas test button
- Wire feed and wire retract buttons
- Integrated gas flow sensor
- Min. flow rate monitoring
- Compressed air blow valve to gun cleaning
- Euro/Power pin -connector versions available
- Back light provided behind drive wheels
- Support for push/pull torches

TECHNICAL SPECIFICATIONS

	A7 Wire Feeder 25	A7 Wire Feeder 25 -PP
Product code	6203510	6203502
Wire feed mechanism	4-roll, two motors	4-roll, two motors
Wire feed speed adjustment	0.5 – 25 m/min	0.5 – 25 m/min
Gun connection	Euro	PP
Filler wire sizes (Fe solid)	0.8 – 1.6 mm	0.8 – 1.6 mm
Filler wire sizes (Fe cored)	1.0 – 1.6 mm	1.0 – 1.6 mm
Filler wire sizes (Ss)	0.8 – 1.6 mm	0.8 – 1.6 mm
Filler wire sizes (Al)	1.0 – 2.4 mm	1.0 – 2.4 mm
Filler wire sizes (CuSi)	0.8 – 1.2 mm	0.8 – 1.2 mm

	A7 Wire Feeder 25	A7 Wire Feeder 25 -PP
Operating voltage (safety voltage)	50 V DC	50 V DC
Operating temperature range	-20 ... +40 °C	-20 ... +40 °C
External dimensions LxWxH	380 × 250 × 170 mm	380 × 250 × 170 mm
Weight (no accessories)	7.8 kg	7.8 kg
Degree of protection	IP21S	IP21S
EMC class	A	A
Storage temperature range	-40 ... +60 °C	-40 ... +60 °C