

Delta+ 90 FreshAir



BENEFITS

- A heavy duty integrated solution offering hard hat welding and grinding protection
- EN 397, EN 175 B, AS/NZS 1801, and AS/NZS 1337.1
- FreshAir Flow control rated to EN 12941 TH2 and AS/NZS 1716
- Welding visor can be fitted with either standard or ADF welding lens
- Impact rated full-face clear visor for exceptional protection and work area visibility
- Positive pressure design makes breathing effortless and safe at all times
- Choose either a battery powered filter pack or a regulated airline supplied breathing air system
- Includes mounting for optional high quality ear defenders

TECHNICAL SPECIFICATIONS

Delta+ 90 FreshAir

Product code	9873068
Air flow	140 - 210 l/min at 8 adjustable flow rates
Weight of the blower unit incl. filter and battery	900 g
Noise level	61 dB
NiMh battery lifetime	500 - 700 charging cycles
One charging cycle	10-14 hours
Belt size	80 - 100 cm
Recommended temperature range	10 - 60 °C
Recommended humidity range	20 - 80 % Rh
Certification	If the requirements of TP-610050-1 are met, it complies with EN 12 021
Weight of the unit	250 g
Inlet connection	Compatible with RECTUS series 23, 26 a CEYN320
Outlet connection	MINI DN 5
Supply pressure range	300 - 1000 kPa
Weight without filter	6300 g
Weight including filter	6800 g
Minimum air flow	170 l/min-1
Maximum air flow	500 l/min