

Flexlite TX - Master M



reddot winner 2020
industrial design



BENEFITS

- Flexible cable set with leather sheathing protection maximizes durability
- Innovative torch design increases user comfort by reducing wrist loading
- Silicone rubber material gives a firm grip on the handle
- Kemppi consumables guarantee high quality and cost-effectiveness for your welding
- Torch models available with or without a trigger switch
- Optional switch extension increases trigger control accuracy

OVERVIEW

Flexlite TX models compatible with MasterMig

Series 3

TX 223GE

TX 253WSE

TX 353WE

In model names: G = Gas-cooled, W = Water-cooled, S = long cable, E = Euro connector

TECHNICAL SPECIFICATIONS

Flexlite TX	TX 223GE	TX 253WSE	TX 353WE
Product code	TX223GE4 (4m)	TX253WSE4 (4m)	TX353WE4 (4m)
Standards	IEC 60974-7	IEC 60974-7	IEC 60974-7
Type of cooling	Gas	Water	Water
Type of connection (Current-gas)	Euro	Euro	Euro
Load capacity @ 40 % (Argon)	220 A	250 A	350 A
Load capacity @ 100 % (Argon)	-	200 A	250 A
Type of connection (Control)	Euro	Euro	Euro
Type of connection (Coolant)	-	Snap connector	Snap connector
Remote control	No	No	No
Neck type	70° angle	Rotating	70° angle