

Kempact 323R



OVERVIEW

Kempci K3 compact welder for cost-efficient MIG/MAG welding, delivering 320 A with a 3-phase 400 V power supply.

Kempact 323R includes a Regular control panel, DuraTorque 4-roll wire drive unit, Flexlite GX welding gun and earth return lead pack.

TECHNICAL SPECIFICATIONS

Kempact 323R

Product code	Kempact 323R, GX 403 G, 3.5m - P2211GX Kempact 323R, GX 303 G, 3.5m - P2229GX, Only 300A/35% range Kempact 323R, GX 403 G, 5m - P2212GX Kempact 323R, GX 303 G, 5m - P2230GX, Only 300A/35% range
Connection voltage 3~ 50/60 Hz	400 V \pm 15%
Fuse (delayed)	10 A
Welding range	10 V/20 A–32.5 V/320 A
Open circuit voltage	40V
Wire feed speed adjustment	1.0 - 20.0 m/min
Filler wire sizes (Fe solid)	0.8...1.2 mm
Filler wire sizes (Fe cored)	0.8...1.2 mm
Filler wire sizes (Ss)	0.8...1.2 mm
Filler wire sizes (Al)	1.0...1.2 mm
Operating temperature range	-20...+40 °C
External dimensions LxWxH	623 × 579 × 1070 mm
Weight (no accessories)	44 kg
Degree of protection	IP23S
Standards	IEC 60974-1, IEC 60974-5, IEC 60974-10