

KempArc SYN 500 Power source



OVERVIEW

Synergic MIG/MAG welding automation system, especially well-suited for cost-effective retrofit cases and heavy duty applications. KempArc SYN 500 is available in digital and analogue (AN) models for integration with different robotic control systems.

TECHNICAL SPECIFICATIONS

KempArc SYN 500 Power source

Product code	KempArc SYN 500 (digital) - 6201500 KempArc SYN 500 (analogue) - 6201500AN
Connection voltage 3~ 50/60 Hz	400 V -15...+20%
Fuse (delayed)	35 A
Minimum generator power	27kVA (60%) 20kVA (100%)
Welding range	10 ... 42 V
Open circuit voltage	50 V
Rated power 60% ED	26,1 kVA
Rated power 100% ED	20,3 kVA
Primary current 50% ED I1max	40,0 A
Primary current 100% ED I1	31,0 A
Connection cable size	6 mm ²
Idle power (no load power)	25 W
Efficiency	87%
Power factor	0,9
Voltage supply for auxiliary devices	50 V
Auxiliary device supply fuse (X14, X15)	6, 3 A delayed
Voltage supply for the cooling device	1-ph 400 VAC/250 VA

KempArc SYN 500 Power source

Max. welding voltage	46 V
Max. output current	500 A (60 %)
Operating temperature range	-20 ... +40 °C
External dimensions LxWxH	590 × 230 × 500 mm
Weight (no accessories)	37 kg
Degree of protection	IP23C
EMC class	A
Storage temperature range	-40 ... +60 °C