

MasterMig 355 GM



OVERVIEW

Compact MIG/MAG welder with manual, synergic (Auto), pulse (Auto Pulse), and double pulse welding options. Provides 350 A with a 40% duty cycle. Intelligent welding parameter setting with Weld Assist. Color LCD display and LED work lights for excellent user experience. Includes work pack welding software programs inc. Fe, Ss, Al, CuSi, CuAl, Fe Metal, Fe Rutil, FC-CrNiMo materials. Generator use and multi-voltage use.

TECHNICAL SPECIFICATIONS

MasterMig 355 GM

Product code	MSM355GM
Connection voltage 3~ 50/60 Hz	220 - 230 V $\pm 10\%$; 380 - 460 V $\pm 10\%$
Output 40% ED	350 A (MMA 330 A); 300 A (MMA 280 A)
Output 60% ED	280 A; 240 A
Output 100% ED	220 A; 190 A
Wire feed mechanism	4-roll, single-motor
Recommended generator power (min)	20 kVA
Gun connection	Euro
Filler wires, Ss	0.8 - 1.2 mm
Filler wires, Al	0.8 - 1.2 mm
Filler wires, Fe	0.8 - 1.2 mm
Filler wires, MC/FC	0.8 - 1.2 mm
Wire feed speed	0.5 - 25 m/min
Diameter of feed rolls	32mm
Welding current and voltage range, MIG	15 A/10 V - 350 A/ 45 V; 15 A/10 V - 300 A/ 40 V
Welding current and voltage range, TIG	15 A/1 V - 350 A/ 45 V; 15 A/1 V - 300 A/ 40 V
Welding current and voltage range, MMA	15 A/10 V - 330 A/ 45 V; 15 A/10 V - 300 A/ 40 V

MasterMig 355 GM

Operating temperature range	-20...+40 °C
External dimensions LxWxH	602 x 298 x 447 mm
Weight (no accessories)	27 kg
Degree of protection	IP23S
Standards	IEC 60974-1, -10
Wire spool weight, max.	20 kg
Wire spool diameter, max.	300 mm
EMC class	A
Storage temperature range	-40...+60 °C
Shielding gas pressure (max)	0.5 MPa