

MinarcTig Evo 200MLP DK



OVERVIEW

The delivery package includes a TTC 220 welding torch (4 m/8 m), cables, gas hose, and shoulder strap.

TECHNICAL SPECIFICATIONS

MinarcTig Evo 200MLP DK

Product code	MinarcTig Evo 200MLP DK, TTC 220, 4 m - P0678 MinarcTig Evo 200MLP DK, TTC 220, 8 m - P0679
Connection voltage 1~ 50/60 Hz	230 V \pm 15%
Fuse (delayed)	16 A
Minimum generator power	5.6kVA
Output (TIG) 35% ED	200 A/18.0 V
Output (TIG) 60% ED	160 A/16.4 V
Output (TIG) 100% ED	140 A/15.6 V
Output (MMA) 35% ED	170 A/26.8 V
Output (MMA) 60% ED	130 A/25.2 V
Output (MMA) 100% ED	110 A/24.4 V
Open circuit voltage	95 V
Stick electrode sizes	1.5...4.0 mm
Welding range (MMA)	10 A/20.4 V...170 A/26.8 V
Welding range (TIG)	5 A/10.2 V...200 A/18.0 V
Operating temperature range	-20...+40 °C
External dimensions LxWxH	449 × 210 × 358 mm
Weight (no accessories)	11 kg
Degree of protection	IP23S
Standards	IEC 60974-1, IEC 60974-3, IEC 60974-10, IEC 61000-3-12