

# PMT MN (MN stands for Multi-Neck)



## BENEFITS

- 320 A gas-cooled fast change neck system
- Extra reach – 3.5 m or 5 m gun lengths
- 5 alternative neck versions
- 40 alternative model specifications
- Low weight and excellent balance
- Easy connection – standard Euro connector
- Root, access, or positional welding

## OVERVIEW

### PMT MN

Filler wires

0.8...1.6  
0.8...1.6  
0.6...1.2  
0.6...1.2  
0.6...1.2  
0.6...1.2  
0.6...1.2  
0.6...1.2  
0.6...1.2  
0.6...1.2  
0.6...1.2

### 3.5 m, ø 1.0 mm

Ordering code

62503230N01  
62503230N01SS  
62503230N05  
62503230N07  
62503230N09  
62503230N03  
62503230N03SS  
62503230N05SS  
62503230N07SS  
62503230N09SS

Neck

Fe, 45°, L222  
Ss, 45°, L222  
Fe, L168, RP  
Fe, 60°, L198  
Fe, 60°, L168  
Fe, L198, RP  
Ss, 60°, L198, RP  
Ss, 60°, L168, RP  
Ss, 60°, L198  
Ss, 60°, L168

### 3.5 m, ø 1.2 mm

Ordering code

62503230N02  
62503230N02SS  
62503230N06  
62503230N08  
62503230N10  
62503230N04  
62503230N04SS  
62503230N06SS  
62503230N08SS  
62503230N10SS

Neck

Fe, 45°/222  
Ss, 45°/222  
Fe, 60°/168, RP  
Fe, 60°/198  
Fe, 60°/168  
Fe, 60°/198, RP  
Ss, 60°/198, RP  
Ss, 60°/168, RP  
Ss, 60°/198  
Ss, 60°/168

### PMT MN

Filler wires

0.8...1.6  
0.8...1.6  
0.6...1.2  
0.6...1.2  
0.6...1.2  
0.6...1.2  
0.6...1.2  
0.6...1.2  
0.6...1.2  
0.6...1.2  
0.6...1.2

### 5 m, ø 1.0 mm

Ordering code

62503250N01  
62503250N01SS  
62503250N05  
62503250N07  
62503250N09  
62503250N03  
62503250N03SS  
62503250N05SS  
62503250N07SS  
62503250N09SS

Neck

Fe, 45°, L222  
Ss, 45°, L222  
Fe, 60°, L168, RP  
Fe, 60°, L198  
Fe, 60°, L168  
Fe, 60°, L198, RP  
Ss, 60°, L198, RP  
Ss, 60°, L168, RP  
Ss, 60°, L198  
Ss, 60°, L168

### 5 m, ø 1.2 mm

Ordering code

62503250N02  
62503250N02SS  
62503250N06  
62503250N08  
62503250N10  
62503250N04  
62503250N04SS  
62503250N06SS  
62503250N08SS  
62503250N10SS

Neck

Fe, 45°/222  
Ss, 45°/222  
Fe, 60°/168, RP  
Fe, 60°/198  
Fe, 60°/168  
Fe, 60°/198, RP  
Ss, 60°/198, RP  
Ss, 60°/168, RP  
Ss, 60°/198  
Ss, 60°/168

RP= Root pass, Ss models with Chili liner, Fe models with spiral liner. All packages air-cooled, load capacity 320 A @ 35% A (Ar + CO?)