

SuperSnake GT02S/GT02SW - subfeeder



BENEFITS

- Suitable for Fe/Ss/Al/FMC/MCW filler wires
- Includes voltage and wire speed adjustment
- Large, clear meter display
- Brights™ LED cabinet lighting
- 10-, 15-, 20-, 25-meter air- and water-cooled models
- Visible safety with tough, bright orange casing
- Gun remote control option

TECHNICAL SPECIFICATIONS

SuperSnake	SuperSnake GT02S	SuperSnake GT02SW	SuperSnake GT02SC (Gas)	SuperSnake GT02SWC (Water)
Product code	6153100	6154100		
Ordering code 10m	6153100	6154100		
Ordering code 15m	6153150	6154150	61531501	61541501
Ordering code 20m	6153200	6154200		61542001
Ordering code 25m	6153250	6154250		
MXF synchronisation kit	W004030	W004030		
SuperSnake protection frame	6185276	6185276		

SuperSnake

Description	subfeeder
Output 60% ED	380 A
Wire feed mechanism	2-roll
Wire feed speed	0...25 m/min
Feeder body dimensions, L x W x H	102 x 371 x 138
Wire recommendation, 25m Solid Fe/Ss	1.0...1.6 mm
Wire recommendation, 25m Al alloys	1.2...1.6 mm
Wire recommendation, 25m, FCW/MCW	1.2...1.6 mm
Cable diameter	50 mm ²
Supply voltage	50 VDC
Protection class	IP23S