

WS gun range



BENEFITS

- Great distance – No motor drive – Lower cost
- Model options – 300 A to 420 A
- No special equipment modification
- Easy connection – standard Euro connector
- Superb for Aluminum and Stainless Steel
- Uses Kemppi Patented DL Chili liner technology

TECHNICAL SPECIFICATIONS

WS gun range	WS 35	WS 30W	WS 42W
Product code	6253516A12	6253046A12	6254206A12
Cooling	Gas	Water	Water
Filler wires, Ss	1.0 mm	1.0...1.2 mm	1.0...1.2 mm
Filler wires, Al	1.2 mm	1.2 (1.6 mm)	1.2 (1.6 mm)
Length / ordering code 6m, Al 1.2	6253516A12	6253046A12	6254206A12
Length / ordering code 6m, Ss 1.0	6253516S10	6253046S10	6254206S10
Length / ordering code 6m, Ss 1.2		6253046S12	6254206S12
Length / ordering code 8m, Al 1.2		6253048A12	6254208A12
Length / ordering code 8m, Ss 1.0		6253048S10	6254208S10
Length / ordering code 8m, Ss 1.2		6253048S12	6254208S12
Load capacity, Ar + CO2 (35%)	300 A		
Load capacity, Ar + CO2 (100%)		250 A	300 A