

# X5 Wire Feeder 300 Auto+



## BENEFITS

- Top-loading wire feeder ensures ergonomics in wire spool changes
- Easy-to-use graphical, 5.7" TFT screen panel for synergic operation
- Designed for MIG/MAG, TIG, MMA, and gouging processes
- Automatic parameter adjustment saves time in welding preparations
- 4-wheel wire feed mechanism with integrated lighting and a kinetic spool brake ensures a steady and reliable wire feed
- USB port and Bluetooth connectivity for convenient system software updates
- Rotameter included as standard for regulating the shielding gas flow
- Enables the use of Wise special processes for excellent welding quality

This wire feeder model can be used with **SuperSnake GT02S/ GT02SW** when extended welding reach or support for distance wire feed is required. Please note that the compatibility is limited to motor synchronicity only.

## TECHNICAL SPECIFICATIONS

### X5 Wire Feeder 300 Auto+

Product code	X5200300000
Wire feed mechanism	4-roll, single-motor
Gun connection	Euro
Filler wires	Fe 0.8 ... 2.0 mm Ss 0.8 ... 2.0 mm Mc/Fc 0.8 ... 2.4 mm Al 0.8 ... 2.4 mm
Wire feed speed	0.5 ... 25 m/min
Diameter of feed rolls	32 mm
Operating temperature range	-20...+40 °C
External dimensions LxWxH	650 x 230 x 410 mm
Weight (no accessories)	10.9 kg
Degree of protection	IP23S
Wire spool weight, max.	20.0 kg
Wire spool diameter, max.	300 mm
EMC class	A
Storage temperature range	-40...+60 °C
Shielding gas pressure (max)	0.5 MPa
Welding current, 60 %	500 A
Welding current, 100 %	430 A