

X5 Wire Feeder HD300 APC



OVERVIEW

Side-loading wire feeder with a graphical, 5.7" TFT display panel. For synergic MIG/MAG, TIG, MMA, and gouging. Automatic parameter adjustment. 4-wheel wire feed mechanism with integrated lighting and a kinetic spool brake. Impact-resistant cabinet. USB port connectivity. Cabinet lights and LED work lights for excellent user experience. Embedded connectivity to WLAN, supporting the digital WPS and WeldEye ArcVision module. Enables the use of Wise special processes and SuperSnake GTX subfeeder (motor power and sync only).

TECHNICAL SPECIFICATIONS

X5 Wire Feeder HD300 APC

Product code	X5280300000
Wire feed mechanism	4-roll, single-motor
Gun connection	Euro
Filler wires	Fe 0.8 ... 2.0 mm Ss 0.8 ... 2.0 mm Mc/Fc 0.8 ... 2.4 mm Al 0.8 ... 2.4 mm
Wire feed speed	0.5 ... 25 m/min
Diameter of feed rolls	32 mm
Operating temperature range	-20...+40 °C
External dimensions LxWxH	670 x 240 x 465 mm
Weight (no accessories)	14.4 kg
Degree of protection	IP23S
Wire spool weight, max.	20 kg
Wire spool diameter, max.	300 mm
EMC class	A
Storage temperature range	-40...+60 °C
Shielding gas pressure (max)	0.5 MPa
Welding current, 60 %	500 A

X5 Wire Feeder HD300 APC

Welding current, 100 %

430 A