

X5 Wire Feeder HD300 M



OVERVIEW

Side-loading wire feeder with a digital parameter display. For MIG/MAG, MMA, and gouging. Manual, 2-knob parameter control. 4-wheel wire feed mechanism with integrated lighting and a kinetic spool brake. Impact-resistant cabinet. USB port connectivity. Cabinet lights and LED work lights for excellent user experience. Enables the use of SuperSnake GTX sub feeder and HR45 remote control.

TECHNICAL SPECIFICATIONS

X5 Wire Feeder HD300 M

| | |
|------------------------------|--|
| Product code | X5260300000 |
| Wire feed mechanism | 4-roll, single-motor |
| Wire feed speed | 0.5 ... 25 m/min |
| Gun connection | Euro |
| Wire spool weight, max. | 20 kg |
| Wire spool diameter, max. | 300 mm |
| Filler wires | Fe 0.8 ... 2.0 mm Ss 0.8 ... 2.0 mm Mc/Fc 0.8 ... 2.4 mm Al 0.8 ... 2.4 mm |
| Diameter of feed rolls | 32 mm |
| Operating temperature range | -20...+40 °C |
| External dimensions LxWxH | 670 x 240 x 465 mm |
| Weight (no accessories) | 14.4 kg |
| Degree of protection | IP23S |
| EMC class | A |
| Storage temperature range | -40...+60 °C |
| Shielding gas pressure (max) | 0.5 MPa |
| Welding current, 60 % | 500 A |
| Welding current, 100 % | 430 A |