

X8 MIG Gun 420-w



OVERVIEW

Available in 3.5 and 5 meters, and as a WeldSnake model in 8 meters. Wire diameter 0.8–1.6 mm (1.2–1.6 mm for WS model).

TECHNICAL SPECIFICATIONS

X8 MIG Gun 420-w

Product code	X8300423500 - X8 MIG Gun 420-w 3,5 m X8300425000 - X8 MIG Gun 420-w 5,0 m X8300428000 - X8 MIG WS Gun 420-w, 8,0 m
Gun connection	Kemppi
Cooling	Liquid
Filler wires, Ss	0.8/0.9/1.0/1.2/1.4/1.6 (WS 1.2/1.4/1.6)
Filler wires, Al	0.8/0.9/1.0/1.2/1.4/1.6 (WS 1.4/1.6)
Filler wires, Fe	0.8/0.9/1.0/1.2/1.4/1.6 (WS 1.2/1.4/1.6)
Filler wires, Fe-MC/FC	0.9/1.0/1.2/1.4/1.6 (WS 1.2/1.4/1.6)
Filler wires, Ss-MC/FC	0.9/1.0/1.2/1.4/1.6 (WS 1.2/1.4/1.6)
Load capacity @ 100 % (Mixed gas)	420 (WS 300)
Neck angles	50
Changeable neck	No
Rotating neck	No
Pistol grip handle	Yes
Operating temperature range	-20...+40 °C
Standards	IEC 60974-7