

X8 Power Source 400 MV



PANORAMICA

Provides 400 A with a 60% duty cycle. The multi-voltage power source is suitable for the most common electrical network voltages. Control Pad always included with the power source. X8 Cooler not included.

SPECIFICHE TECNICHE

X8 Power Source 400 MV

Codice prodotto	X8100400101 - X8 Power Source 400 MV, CUSTOM (Work Pack + WiseFusion)
Tensione di collegamento alla rete elettrica 3~ 50/60 Hz	220 - 230 V ± 10 % 380 - 460 V ± 10 %
Fusibile	32 A
Fusibile, 380 - 460 V	63 A
Potenza a circuito aperto (MMA) (senza unità di raffreddamento e trainafile, ventole OFF)	44 - 53 W
Potenza a circuito aperto (MMA) (senza unità di raffreddamento e trainafile, ventole ON)	99 - 111 W
Erogazione 60% ED	400 A
Erogazione 100% ED	320 A
Intervallo di regolazione corrente e tensione di saldatura, MIG a 220 V	20 A/14 V - 400 A/50 V
Intervallo di regolazione corrente e tensione di saldatura, MIG a 380 V	20 A/14 V - 400 A/50 V
Intervallo di regolazione corrente e tensione di saldatura, MMA a 220 V	15 A/20 V - 400 A/58 V
Intervallo di regolazione corrente e tensione di saldatura, MMA a 380 V	15 A/20 V - 400 A/58 V
Potenza del generatore consigliata (min)	35 kVA
Tensione a vuoto (MMA)	50 V
Intervallo temperatura di esercizio	-20...+40 °C
Dimensioni esterne Lu x La x H	921 x 348 x 795 mm

X8 Power Source 400 MV

Peso (senza accessori)

95 kg