

X8 Power Source 400



OVERZICHT

Provides 400 A with a 60% duty cycle. Can be ordered with or without X8 Cooler. Control Pad always included with the power source.

TECHNISCHE SPECIFICATIES

X8 Power Source 400

Productcode	X8100400001 - X8 Power Source 400, CUSTOM (Work Pack + WiseFusion) X8100401000 - X8 Power Source 400, cooler X8100401001 - X8 Power Source 400, cooler, CUSTOM (Work Pack + WiseFusion)
Aansluitspanning 3~ 50/60 Hz	380 - 460 V \pm 10 %
Zekering	32 A
Nullastvermogen (MMA) (zonder koeler en draadaanvoerunit, ventilators uit)	44 - 53 W
Nullastvermogen (MMA) (zonder koeler en draadaanvoerunit, ventilators aan)	107 - 111 W
Nullastvermogen (MMA) (met koeler, zonder draadaanvoerunit, ventilators aan)	132 - 137 W
Belastbaarheid 60% ID	400 A
Belastbaarheid 100% ID	320 A
Bereik lasstroom- en -spanning, MIG bij 380 V	20A/14V - 400A/50V
Bereik lasstroom- en -spanning, MMA bij 380 V	15A/20V - 400A/58V
Aanbevolen generatorvermogen (min)	25 kVA
Open spanning (MMA)	50 V
Temperatuurbereik voor bediening	-20...+40 °C
Buitenafmetingen (l x b x h)	921 x 348 x 795 mm
Gewicht (zonder accessoires)	95 kg