

X8 Power Source 600 MV



OVERSIKT

Provides 600 A with a 40% duty cycle. The multi-voltage power source is suitable for the most common electrical network voltages. Requires a 63 A plug. Control Pad and X8 Cooler always included with the power source.

TEKNISKE SPESIFIKASJONER

X8 Power Source 600 MV

Produktkode	X8100601100 (Incl. X8 Control Pad and X8 Cooler) Power upgrade 600 for X8 Power Source - X8560000
Strømtilkoblingsspenning 3- 50/60 Hz	220 - 230 V ± 10 % 380 - 460 V ± 10 %
Sikring, 380 – 460 V	35 A
Åpen krets-strøm (MMA) (uten kjøler og trådmater, vifter AV)	44 - 53 W
Åpen krets-strøm (MMA) (uten kjøler og trådmater, vifter PÅ)	99 - 111 W
Åpen krets-strøm (MMA) (med kjøler, uten trådmater, vifter PÅ)	121 - 137 W
Ytelse 40 % ED	600 A
Ytelse 60 % ED	530 A
Ytelse 100 % ED	440 A
Sveisestrøm og spenningsområde, MIG @ 220 V	10A/10V - 600A/47V
Sveisestrøm og spenningsområde, MIG @ 380 V	10A/10V - 600A/57V
Sveisestrøm og spenningsområde, MMA @ 220 V	10A/10V - 600A/47V
Sveisestrøm og spenningsområde, MMA @ 380 V	10A/10V - 600A/58.5V
Anbefalt generatorstrøm (min)	40 kVA
Åpen krets-spenning (MMA)	50 V
Utvendige mål LxBxH	921 x 348 x 795 mm
Vekt (uten tilbehør)	95 kg

X8 Power Source 600 MV

Driftstemperaturområde	-20...+40 °C
Sikring, 220–230 V	63 A