

X8 Power Source 500 MV



ÖVERSIKT

Provides 500 A with a 60% duty cycle. The multi-voltage power source is suitable for the most common electrical network voltages. Control Pad and X8 Cooler always included with the power source.

TEKNISKA DATA

X8 Power Source 500 MV

Produktkod	X8100501100 - X8 Power Source 500 MV, cooler X8100501101 - X8 Power Source 500 MV, cooler, CUSTOM (Work Pack + WiseFusion)
Anslutningsspänning 3-fas 50/60 Hz	220 - 230 V ± 10 % 380 - 460 V ± 10 %
Säkring	32 A
Säkring, 380–460 V	63 A
Tomgångseffekt (MMA) (utan kylare och trådmatarverk, fläktar AV)	44 - 53 W
Tomgångseffekt (MMA) (utan kylare och trådmatarverk, fläktar PÅ)	99 - 111 W
Tomgångseffekt (MMA) (med kylare, utan trådmatarverk, fläktar PÅ)	121 - 137 W
Uteffekt 60 % ED	500 A
Uteffekt 100 % ED	400 A
Svetsström och spänningsområde, MIG @ 220 V	20A/14V - 500A/55V
Svetsström och spänningsområde, MIG @ 380 V	20A/14V - 500A/55V
Svetsström och spänningsområde, MMA @ 220 V	15A/20V - 500A/57V
Svetsström och spänningsområde, MMA @ 380 V	15A/20V - 500A/57V
Rekommenderad elverkseffekt (min.)	35 kVA
Tomgångsspänning (MMA)	50 V
Omgivningstemperatur	-20...+40 °C
Yttermått L x B x H	921 x 348 x 795 mm

X8 Power Source 500 MV

Vikt (inga tillbehör)

95 kg