

X8 Power Source 500 MV



概览

Provides 500 A with a 60% duty cycle. The multi-voltage power source is suitable for the most common electrical network voltages. Control Pad and X8 Cooler always included with the power source.

技术规格

X8 Power Source 500 MV		
产品代码	X8100501100 - X8 Power Source 500 MV, cooler X8100501101 - X8 Power Source 500 MV, cooler, CUSTOM (Work Pack + WiseFusion)	
电源连接电压 3~ 50/60 Hz	220 - 230 V $\pm$ 10 % 380 - 460 V $\pm$ 10 %	
保险丝	32 A	
保险丝, 380 - 460 V	63 A	
空载功率 (MMA) (不带冷却器和送丝机, 风扇关闭)	44 - 53 W	
空载功率 (MMA) (不带冷却器和送丝机, 风扇打开)	99 - 111 W	
空载功率 (MMA) (带冷却器, 不带送丝机, 风扇打开)	121 - 137 W	
输出 60% ED	500 A	
输出 100% 暂载率	400 A	
焊接电流和电压范围, MIG @ 220 V	20A/14V - 500A/55V	
焊接电流和电压范围, MIG @ 380 V	20A/14V - 500A/55V	
焊接电流和电压范围, MMA @ 220 V	15A/20V - 500A/57V	
焊接电流和电压范围, MMA @ 380 V	15A/20V - 500A/57V	
建议的发电机功率 (最小)	35 kVA	
空载电压 (MMA)	50 V	
工作温度范围	-20...+40 °C	
外部尺寸 (长 x 宽 x 高)	921 x 348 x 795 mm	

X8 Power Source 500 MV

重量（无配件）	95 kg
---------	-------